

## Pro Series Gooseneck Highboy Trailer w/Full Tilt - 20,000lb-30,000lb GVW

Ordered By: \_\_\_\_\_

Dealer: \_\_\_\_\_

PO#: \_\_\_\_\_

Date: \_\_\_\_\_

### Standard Features:

<b>Coupler:</b>	Adjustable GN Ball Coupler	<b>Lace Rail:</b>	Channel - 5" w/Pockets & Rubrail
<b>Safety Chains:</b>	3/8" Grade 70 w/Grab Hooks	<b>Cmembers:</b>	Channel - 3" on 16" Centers
<b>Width:</b>	102" Overall	<b>Wiring:</b>	Arctic Wiring, Soldered & Enclosed in Conduit
<b>Deck Height:</b>	36"	<b>Lights:</b>	LED, Rubber Mounted (30' + c/w Side Signal)
<b>Axles:</b>	Electric Brakes, Grease Hubs, 8 Stud	<b>Decking:</b>	Spruce - 2" Treated
<b>Suspension:</b>	Leaf Springs w/Equalizers	<b>Toolbox:</b>	TB4 Riser Toolbox (upright)
<b>Tires &amp; Rims:</b>	10 Ply Tires w/Grey Dual Rims	<b>Steps:</b>	Each Side w/Grab Handles
<b>Main Frame:</b>	Wide Flange Beam (See Below)	<b>Finish:</b>	Sand Blast, Prime, Paint w/PPG Urethane

### MODEL:

Quantity:

**\*\*NOTE\*\* Only one type of trailer per order form.**

Select Model	Main Frame	Axle Size	Tire & Rim	Tare Weight	Carrying Capacity	Landing Gear
GHB208-30FT	12@16lb	2:10,000lb	235/80R16	7550lb	17450lb	2:12,000lb
GHB208-32FT	12@16lb	2:10,000lb	235/80R16	7858lb	17142lb	2:12,000lb
GHB208-34FT	12@16lb	2:10,000lb	235/80R16	8166lb	16834lb	2:12,000lb
GHB208-36FT	12@19lb	2:10,000lb	235/80R17	8474lb	16526lb	2:12,000lb
GHB208-38FT	12@19lb	2:10,000lb	235/80R18	8782lb	16218lb	2:12,000lb
GHB208-40FT	12@19lb	2:10,000lb	235/80R16	9090lb	15910lb	2:12,000lb
GHB208-42FT	12@19lb	2:10,000lb	235/80R16	9398lb	15602lb	2:12,000lb

### OPTIONS:

<b>210HS =</b>	2-10000Lb Hyd/Spr	<b>PS1 =</b>	Pipe spools (between pockets)
<b>212ES =</b>	2-12000Lb Elec/Spr	<b>W4 =</b>	Weld on 3 bar winch
<b>212HS =</b>	2-12000Lb Hyd/Spr	<b>W4S =</b>	Sliding 3 bar winch
<b>215ES =</b>	2-15000Lb Elec/Spr	<b>SWT =</b>	Sliding winch track
<b>215HS =</b>	2-15000Lb Hyd/Spr	<b>W4P =</b>	Removable 3 bar wncH
	<b>30,000LB + GVW c/w 6" lace rail</b>	<b>R4W =</b>	Weld on - 4" D ring
<b>SS2 =</b>	HDSS Suspension (10k+)	<b>R4R =</b>	Removable 4" D ring
<b>SP4 =</b>	Spare-ST235/80R16-10ply-dual	<b>PS =</b>	Pocket stakes 13"
<b>SP6 =</b>	Spare-ST235/85R16-14ply-dual	<b>P4X =</b>	4ea extra stake pockets
<b>SP10 =</b>	Spare-ST215/75R17.5-16ply-dual	<b>P1X =</b>	Additional-Stake Pockets
<b>USP5 =</b>	ST235/85R16-14ply Upgrade	<b>TB2 =</b>	24" side mount toolbox
	<b>18 Ply Available on 15k Axles Only</b>	<b>TB2A =</b>	36" Side Mount Toolbox
<b>USP8 =</b>	ST235/75R17.5-18ply-dual-upgrade	<b>TB6 =</b>	48" Side Mount Toolbox
<b>SP8 =</b>	Spare-ST235/75R17.5-18ply-dual	<b>DR1 =</b>	8' Dunnage Rack
<b>JH2T =</b>	2-hyd Jacks w/o Power Pack	<b>LR2 =</b>	2" Rough Lumber (Pertrudes 1/2")
<b>J3 =</b>	2-12k 2spd	<b>LTG =</b>	1 3/8" T&G Fir Lumber
<b>J5 =</b>	2-25k 2spd	<b>SM1 =</b>	Spare Tire Mount (Foldup)
<b>GKP =</b>	GN King Pin	<b>LT1 =</b>	Led Light Bar In Neck
<b>GB3 =</b>	GN Ball 3"	<b>LT2 =</b>	Led Work Light (Sides Of Neck)
<b>NR6 =</b>	Raise Neck 4"	<b>SL =</b>	Lights by Steps
<b>UD =</b>	Upper Deck 102"X 96"	<b>SL1 =</b>	SLS strobe lights w switch
<b>WM1 =</b>	Winch Mount (plate)	<b>CM1 =</b>	12" OC Crossmembers

<b>W17 =</b>	17.5K Winch Pkg c/w Battery	<b>RW1 =</b>	Winch Roller 3" Pipe
<b>P5 =</b>	Quick Connect Power Cable	<b>F2 =</b>	Upgrade-I beam-next size up
<b>P6 =</b>	Solar Panel	<b>DH =</b>	Document Holder
<b>CW2 =</b>	Quick Charge- 12v (20amp)	<b>PG =</b>	Charcoal Grey
<b>CW1 =</b>	110 Inverter Charger	<b>PDA =</b>	Double A Red
<b>AB1 =</b>	Additional Battery	<b>WRK =</b>	Wireless remote for Powerpack
<b>CP7 =</b>	Commercial Plug		
<b>Notes:</b>			
			<b>Signature:</b>