



EXCEL Series

Equipment Trailer - 14000lb GVW

Ordered By: _____

Dealer: _____

PO#: _____

Date: _____

Standard Features:

Coupler:	2-5/16" Adjustable Channel Mount	Fenders:	14 ga Tread Plate
Safety Chains:	5/16" Grade 70 w/Grab Hooks	Pockets:	Preformed - 3/16", no rub rail
Width:	102" Overall , 83" Between Fenders	Cmembers:	Channel - 3" on 24" centers
Deck Height:	26-27"	Wiring:	Arctic Wiring, Soldered & Enclosed in Conduit
Axles:	Electric Brakes, Grease Hubs, 8 Stud	Lights:	LED, Rubber Mounted
Suspension:	Leaf Springs w/Equalizers	Decking:	Spruce - 2" Treated
Tires & Rims:	10 Ply Tires w/White Modular Rims	Toolbox:	Not Included
Main Frame:	Channel (See Below)	Finish:	Sand Blast, Prime, Paint w/PPG Urethane
Ramps:	5' Slide in Standard	Rear Stabilizers:	Not Included

MODEL:

Quantity:	**NOTE** Only one type of trailer per order form.					
Select Model	Main Frame	Axle Size	Tire & Rim	Tare Weight	Carrying Capacity	Landing Gear
EEQ147-14	6" Channel	2:7000lb	235/80R16	2365lb	13191lb	1:8,000lb
EEQ147-16	6" Channel	2:7000lb	235/80R16	2505lb	13051lb	1:8,000lb
EEQ147-18	6" Channel	2:7000lb	235/80R16	2620lb	12936lb	1:8,000lb
EEQ147-20	6" Channel	2:7000lb	235/80R16	2804lb	12688lb	1:8,000lb
EEQ147-22	6" Channel	2:7000lb	235/80R16	2910lb	12576lb	1:8,000lb
EEQ147-24	6" Channel	2:7000lb	235/80R16	3044lb	12436lb	1:8,000lb

OPTIONS:

CPR = Channel Mount Pintle Ring	DT2 = 2' Dovetail w Tread Plate
PDA = Double A Red	SRU5 = 5' Stand Up Ramps
PG = Charcoal Grey	SM2 = Side spare Mount (Weld on)
W4P = Removable 3 bar winch	SM3 = Side spare Mount (Removeable)
R3W = Weld On - 3" D Ring	RS1 = Rear Stabilizers (Tube)
R4W = Weld On - 4" D Ring	RS3 = Rear Stabilizer Jacks (7k Jack)
R4R = Removable 4" D ring	DH = Document Holder
R3R = Removable 3" D ring	ERR = Add Rub Rail to Excel
SP3 = Spare-ST235/80R16-10ply-single	J2 = 1-12k Jack
SP5 = Spare-ST235/85R16-14ply-single	AW2 = Alum wheel upgrade-16"
USP5 = ST235/85R16-14ply Upgrade	TB1 = A Frame Toolbox

Notes:

Signature: _____