

## **EXCEL** Series

## **Economy Trailers 3,500lb-5,000lb GVW**

Ordered By:					Dealer:				
PO#:					Date:	): 			
Standard Fe	atures:								
Coupler:	2" A Frame Coupler				Main Frame:	3" Channel or Preformed (See Below)			
Safety Chains:	1/4" Grade 70 w/Grab Hooks				Fenders:	14 ga Tread Plate			
Vidth:	See Below				Tie downs:	Welded to Outside of Box, Inside of Box			
Deck Height:	21"				Wiring:	Arctic Wiring, Soldered & Enclosed in Conduit			
\xles:	1:3500lb , Idler, Grease Hubs, 5 Stud				Lights:	LED, Rubber Mounted			
Suspension:	Double Eye 4 Leaf				Decking:	Spruce - 2" Treated			
Tires & Rims:	8 Ply Tires w/Modular Rims				Finish:	Sand Blast, Prime, Paint w/PPG Urethane			
Rear Stabilizers: N/A					Ramps:	Not Included			
MODEL:									
Quantity:			E** Only one	type of trailer per order form.					
Select Model	Side Height	Main Frame/Sides	Inside Width	Tire & Rim	Tare Weight	Carrying Ca	apacity	Landing	Gate
EEC35-10	12"	pre/14G	60"	205/75R15	950lb	2 Yards/ 2,	805lbs	1:2000lb	brdbracket
EEC36-12	12"	3"C/14G	72"	205/75R15	1250lb	2.5 Yards/ 2	,475lbs	1:2000lb	brdbracket
<b>OPTIONS:</b>									
135ES =	1-3500Lb Elec/Spr				G4A =	: 4' ramp gate/spr asst			
150IS =	1-5000Lb Idler/Spr				R3W =	Weld on - 3" D ring			
150ES =	1-5000Lb Elec/Spr				WER =	Weed Eater Rack			
SP1 =	Spare-205/75R15-8ply (3500Lb)				PDA =	Double A Red			
SP2 =	Spare-ST225/75R15-8ply (5000Lb)				PG =	Charcoal Grey			
AW1 =	Alum wheel upgrade-15"				BPR =	Boat Posts & Rail			
ABM =	2 5/16" Adjustable Coupler				DH =	Document Holder			
Notes:									
						Signature:			