



# Pro Series

## Highboy Trailer 20,000lb-30,000lb GVW

Ordered By: \_\_\_\_\_

Dealer: \_\_\_\_\_

PO#: \_\_\_\_\_

Date: \_\_\_\_\_

### Standard Features:

<b>Coupler:</b>	Adjustable Flat Mount Pintle Ring	<b>Lace Rail:</b>	Channel - 5" w/Pockets & Rubrail
<b>Safety Chains:</b>	5/16" Grade 70 w/Grab Hooks	<b>Cmembers:</b>	Channel - 3" on 16" Centers
<b>Width:</b>	102" Overall	<b>Wiring:</b>	Arctic Wiring, Soldered & Enclosed in Conduit
<b>Deck Height:</b>	38"	<b>Lights:</b>	LED, Rubber Mounted (30' + c/w Side Signal)
<b>Axes:</b>	Electric Brakes, Grease Hubs, 8 Stud	<b>Decking:</b>	Spruce - 2" Treated
<b>Suspension:</b>	Leaf Springs w/Equalizers	<b>Toolbox:</b>	Not Included
<b>Tires &amp; Rims</b>	10 Ply Tires w/ Dual Rims	<b>Steps:</b>	Not Included
<b>Main Frame:</b>	Wide Flange Beam (See Below)	<b>Finish:</b>	Sand Blast, Prime, Paint w/PPG Urethane
<b>Rear Stabilizers:</b>	Not Included	<b>Ramps:</b>	Not Included

### MODEL:

Quantity:

**\*\*NOTE\*\* Only one type of trailer per order form.**

Select Model	Main Frame	Axle Size	Tire & Rim	Tare Weight	Carrying Capacity	Landing Gear
HB208-24	12@16lb	2:10000lb	235/80R16	5974lb	16248lb	2:12,000lb
HB208-26	12@16lb	2:10000lb	235/80R16	6258lb	15964lb	2:12,000lb
HB208-28	12@16lb	2:10000lb	235/80R16	6558lb	15664lb	2:12,000lb
HB208-30	12@16lb	2:10000lb	235/80R16	6850lb	15372lb	2:12,000lb
HB208-32	12@16lb	2:10000lb	235/80R16	7158lb	15064lb	2:12,000lb
HB208-34	12@16lb	2:10000lb	235/80R16	7466lb	14756lb	2:12,000lb
HB208-36	12@19lb	2:10000lb	235/80R16	7774lb	14448lb	2:12,000lb

### OPTIONS:

<b>210HS =</b>	2-10000Lb Hyd/Spr	<b>R7HD =</b>	7' HD Slide In Ramps
<b>310ES =</b>	3-10000Lb Elec/Spr	<b>R7 =</b>	7' Slide In Ramps
<b>310HS =</b>	3-10000Lb Hyd/Spr	<b>BT7 =</b>	5' BT Conquer Ramps, F Width/Spr Asst
	<i>(Triple Axle Requires F2 Beam Upgrade)</i>	<b>PS1 =</b>	Pipe Spools (Between Pockets)
<b>SS2 =</b>	HDSS Suspension (10k+)	<b>W4 =</b>	Weld on 3 Bar Winch
<b>SS3 =</b>	HDSS suspension (10k+ tridem)	<b>W4S =</b>	Sliding 3 Bar Winch
<b>SP4 =</b>	Spare-ST235/80R16-10ply-dual	<b>SWT =</b>	Sliding Winch Track
<b>SP6 =</b>	Spare-ST235/85R16-14ply-dual	<b>W4P =</b>	Removable 3 Bar Winch
<b>USP5 =</b>	ST235/85R16-14ply Upgrade	<b>R4W =</b>	Weld on 4" D Ring
<b>J3 =</b>	2-12k 2spd	<b>R4R =</b>	Removable 4" D Ring
<b>J5 =</b>	2-25k 2spd	<b>PS =</b>	Pocket Stakes 13"
<b>WM1 =</b>	Winch Mount (Plate)	<b>P4X =</b>	4ea Extra Stake Pockets
<b>WM2 =</b>	Winch Mount (Receiver)	<b>P1X =</b>	Additional-Stake Pockets
<b>W12 =</b>	12K Winch Pkg c/w Battery	<b>TB2 =</b>	24" Side Mount Toolbox
<b>W17 =</b>	17.5K Winch Pkg c/w Battery	<b>TB2A =</b>	36" Side Mount Toolbox
<b>P6 =</b>	Solar Panel	<b>TB6 =</b>	48" Side Mount Toolbox
<b>CW2 =</b>	Quick Charge- 12v (20amp)	<b>TB1 =</b>	A Frame Toolbox
<b>CW1 =</b>	110 Inverter Charger	<b>DR1 =</b>	8' Dunnage Rack
<b>AB1 =</b>	Additional Battery	<b>PDA =</b>	Double A Red
<b>CP7 =</b>	Commercial Plug	<b>PG =</b>	Charcoal Grey
<b>CM1 =</b>	12" OC Crossmembers	<b>DH =</b>	Document Holder
<b>FBM =</b>	Flat Mount Ball (20,000Lb GVW Only)	<b>F2 =</b>	Upgrade-I beam-next size up
<b>RS1 =</b>	Rear Stabilizers (Tube)	<b>RS3 =</b>	Rear Stabilizer Jacks (7k Jack)

Notes:


	<b>Signature:</b>