



Pro Series

Equipment Trailer 14,000lb GVW

Ordered By: _____

Dealer: _____

PO#: _____

Date: _____

Standard Features:

Coupler:	2-5/16" Adjustable Channel Mount	Fenders:	14 ga Tread Plate
Safety Chains:	5/16" Grade 70 w/Grab Hooks	Pockets:	Preformed - 3/16" w/Full Length 1/4" Rubrail
Width:	102" Overall, 83" Between Fenders	Cmembers:	Channel - 3" on 18" Centers
Deck Height:	26"-27"	Wiring:	Arctic Wiring, Soldered & Enclosed in Conduit
Axles:	Electric Brakes, Grease Hubs, 8 Stud	Lights:	LED, Rubber Mounted
Suspension:	Leaf Springs w/Equalizers	Decking:	Spruce - 2" Treated
Tires & Rims	10 Ply Tires w/Modular Rims	Toolbox:	Not Included
Main Frame:	Channel (See Below)	Finish:	Sand Blast, Prime, Paint w/PPG Urethane
Ramps:	5' Slide in Standard	Rear Stabilizers:	RS1 Included

MODEL:

Quantity: _____

****NOTE** Only one type of trailer per order form.**

Select Model	Main Frame	Axle Size	Tire & Rim	Tare Weight	Carrying Capacity	Landing Gear
EQ147-14	6" Channel	2:7000lb	235/80R16	2365lb	13191lb	1:12,000lb
EQ147-16	6" Channel	2:7000lb	235/80R16	2505lb	13051lb	1:12,000lb
EQ147-18	6" Channel	2:7000lb	235/80R16	2620lb	12936lb	1:12,000lb
EQ147-20	7" Channel	2:7000lb	235/80R16	2868lb	12688lb	1:12,000lb
EQ147-22	7" Channel	2:7000lb	235/80R16	2980lb	12576lb	1:12,000lb
EQ147-24	7" Channel	2:7000lb	235/80R16	3120lb	12436lb	1:12,000lb

OPTIONS:

270ET = 2-7000Lb Elec/Tor	DT7 = 3' Dovetail w/ Flip Over Ramps
SWB = Wet Bolt Equalizer (7k axles)	SRU5 = 5' Stand Up Ramps
CPR = Channel Mount Pintle Ring	SRU6 = 6' Stand Up Ramps
SP3 = Spare-ST235/80R16-10ply-single	DT2 = 2' Dovetail w Tread Plate
SP5 = Spare-ST235/85R16-14ply-single	W4P = Removable 3 Bar Winch
USP5 = ST235/85R16-14ply Upgrade	R4W = Weld on - 4" D Ring
AW2 = Alum wheel upgrade-16"	R4R = Removable 4" D Ring
CM1 = 12" OC Crossmembers	P4X = 4ea Extra Stake Pockets
DH = Document Holder	P1X = Additional-Stake Pockets
PG = Charcoal Grey	SM2 = Side spare Mount (Weld on)
PDA = Double A Red	SM3 = Side spare Mount (Removeable)
FG1 = Fender guards (pipe)	TB1 = A Frame Toolbox
FHD3 = Drive over fenders (1/4" cp)	RS3 = Rear Stabilizer Jacks (7k Jack)
WB = 8' Wide Body (CP Wings)	

Notes:

Signature: