



Pro Series Gooseneck Highboy Trailer w/Hydraulic Beavertail 20,000lb-30,000lb GVW

Ordered By: _____

Dealer: _____

PO#: _____

Date: _____

Standard Features:

Coupler:	Adjustable GN Ball Coupler	Lace Rail:	Channel - 5" w/Pockets & Rubrail
Safety Chains:	3/8" Grade 70 w/Grab Hooks	Cmembers:	Channel - 3" on 16" Centers
Width:	102" Overall	Wiring:	Arctic Wiring, Soldered & Enclosed in Conduit
Deck Height:	36"	Lights:	LED, Rubber Mounted (30' + c/w Side Signal)
Axles:	Electric Brakes, Grease Hubs, 8 Stud	Decking:	Spruce - 2" Treated
Suspension:	Leaf Springs w/Equalizers	Toolbox:	TB4 Riser Toolbox (upright)
Tires & Rims:	10 Ply Tires w/Grey Dual Rims	Steps:	Each Side w/Grab Handles
Main Frame:	Wide Flange Beam (See Below)	Finish:	Sand Blast, Prime, Paint w/PPG Urethane

MODEL:

Quantity:

****NOTE** Only one type of trailer per order form.**

Select Model	Main Frame	Axle Size	Tire & Rim	Tare Weight	Carrying Capacity	Landing Gear
GHB208-34HBT	12@16lb	2:10,000lb	235/80R16	8266lb	16734lb	2:12,000lb
GHB208-36HBT	12@19lb	2:10,000lb	235/80R16	8574lb	16426lb	2:12,000lb
GHB208-38HBT	12@19lb	2:10,000lb	235/80R16	8882lb	16118lb	2:12,000lb
GHB208-40HBT	12@19lb	2:10,000lb	235/80R16	9190lb	15810lb	2:12,000lb
GHB208-42HBT	12@19lb	2:10,000lb	235/80R16	9498lb	15502lb	2:12,000lb

OPTIONS:

210HS =	2-10000Lb Hyd/Spr	PS1 =	Pipe spools (between pockets)
212ES =	2-12000Lb Elec/Spr	W4 =	Weld on 3 bar winch
212HS =	2-12000Lb Hyd/Spr	W4S =	Sliding 3 bar winch
215ES =	2-15000Lb Elec/Spr	SWT =	Sliding winch track
215HS =	2-15000Lb Hyd/Spr	W4P =	Removable 3 bar wncH
	30,000LB + GVW c/w 6" lace rail	R4W =	Weld on - 4" D ring
SS2 =	HDSS Suspension (10k+)	R4R =	Removable 4" D ring
SP4 =	Spare-ST235/80R16-10ply-dual	PS =	Pocket stakes 13"
SP6 =	Spare-ST235/85R16-14ply-dual	P4X =	4ea extra stake pockets
USP5 =	ST235/85R16-14ply Upgrade	P1X =	Additional-Stake Pockets
	18 Ply Available on 15k Axles Only	TB2 =	24" side mount toolbox
USP8 =	ST235/75R17.5-18ply-dual-upgrade	TB2A =	36" Side Mount Toolbox
SP8 =	Spare-ST235/75R17.5-18ply-dual	TB6 =	48" Side Mount Toolbox
JH2T =	2-hyd Jacks w/o Power Pack	DR1 =	8' Dunnage Rack
J3 =	2-12k 2spd	LR2 =	2" Rough Lumber (Pertrudes 1/2")
J5 =	2-25k 2spd	LTG =	1 3/8" T&G Fir Lumber
GKP =	GN King Pin	CP3 =	3/16 Steel Checkerplate Full Deck
GB3 =	GN Ball 3"	SM1 =	Spare Tire Mount (Foldup)
NR6 =	Raise Neck 4"	LT1 =	Led Light Bar In Neck
UD =	Upper Deck 102"X 96"	LT2 =	Led Work Light (Sides Of Neck)
WM1 =	Winch Mount (plate)	SL =	Lights by Steps

W17 =	17.5K Winch Pkg c/w Battery	SL1 =	SLS strobe lights w switch
P5 =	Quick Connect Power Cable	CM1 =	12" OC Crossmembers
P6 =	Solar Panel	RW1 =	Winch Roller 3" Pipe
CW2 =	Quick Charge- 12v (20amp)	F2 =	Upgrade-I beam-next size up
CW1 =	110 Inverter Charger	EB =	Engineered Beam
AB1 =	Additional Battery	DH =	Document Holder
CP7 =	Commercial Plug	PG =	Charcoal Grey
WRK =	Wireless remote for Powerpack	PDA =	Double A Red

Notes:

	Signature: