



**Pro Series**

**Gooseneck Highboy Trailer 14,000lb-16,000lb GVW**

Ordered By: \_\_\_\_\_

Dealer: \_\_\_\_\_

PO#: \_\_\_\_\_

Date: \_\_\_\_\_

**Standard Features:**

<b>Coupler:</b>	Adjustable GN Ball Coupler	<b>Lace Rail:</b>	Channel - 5"
<b>Safety Chains:</b>	5/16" Grade 70 w/Grab Hooks	<b>Cmembers:</b>	Channel - 3" on 18" Centers
<b>Width:</b>	102" Overall	<b>Wiring:</b>	Arctic Wiring, Soldered & Enclosed in Conduit
<b>Deck Height:</b>	36"	<b>Lights:</b>	LED, Rubber Mounted (30' + c/w Side Signal)
<b>Axles:</b>	Electric Brakes, Grease Hubs, 8 Stud	<b>Decking:</b>	Spruce - 2" Treated
<b>Suspension:</b>	Leaf Springs w/Equalizers	<b>Toolbox:</b>	Not Included
<b>Tires &amp; Rims</b>	10 Ply Tires w/ Modular Rims	<b>Steps:</b>	Each Side w/Grab Handles
<b>Main Frame:</b>	Wide Flange Beam (See Below)	<b>Finish:</b>	Sand Blast, Prime, Paint w/PPG Urethane
<b>Ramps:</b>	Not Included	<b>Pockets:</b>	Preformed - 3/16" w/Full Length 1/4" Rubrail

**MODEL:**

Quantity:

**\*\*NOTE\*\* Only one type of trailer per order form.**

Select Model	Main Frame	Axle Size	Tire & Rim	Tare Weight	Carrying Capacity	Landing Gear
GHB148-20	10@15lb	2:7000lb	235/80R16	4490lb	11431lb	2:12,000lb
GHB148-22	10@15lb	2:7000lb	235/80R16	4750lb	11138lb	2:12,000lb
GHB148-24	10@15lb	2:7000lb	235/80R16	5040lb	10845lb	2:12,000lb
GHB148-26	10@15lb	2:7000lb	235/80R16	5333lb	10552lb	2:12,000lb
GHB148-28	10@15lb	2:7000lb	235/80R16	5626lb	10259lb	2:12,000lb
GHB148-30	10@15lb	2:7000lb	235/80R16	5919lb	16471lb	2:12,000lb
GHB148-32	10@15lb	2:7000lb	235/80R16	6212lb	16471lb	2:12,000lb

**OPTIONS:**

<b>270ET =</b> 2-7000Lb Elec/Tor	<b>R7HD =</b> 7' HD Slide In Ramps
<b>280ES =</b> 2-8000Lb Elec/Spr	<b>R7 =</b> 7' Slide In Ramps
<b>SWB =</b> Wet Bolt Equalizer (7k axles)	<b>BT7 =</b> 5' BT Conquer Ramps, F Width/Spr Asst
<b>SP3 =</b> Spare-ST235/80R16-10ply-single	<b>PS1 =</b> Pipe Spools (Between Pockets)
<b>SP5 =</b> Spare-ST235/85R16-14ply-single	<b>W4 =</b> Weld on 3 Bar Winch
<b>AW2 =</b> Alum wheel upgrade-16"	<b>W4S =</b> Sliding 3 Bar Winch
<b>USP5 =</b> ST235/85R16-14ply Upgrade	<b>SWT =</b> Sliding Winch Track
<b>J3 =</b> 2-12k 2spd	<b>W4P =</b> Removable 3 Bar Winch
<b>GKP =</b> GN King Pin	<b>R4W =</b> Weld on 4" D Ring
<b>NR4 =</b> Raise Neck 4"	<b>R4R =</b> Removable 4" D Ring
<b>UD =</b> Upper Deck 102" x 96"	<b>PS =</b> Pocket Stakes 13"
<b>WM1 =</b> Winch Mount (Plate)	<b>P4X =</b> 4ea Extra Stake Pockets
<b>W17 =</b> 17.5K Winch Pkg c/w Battery	<b>P1X =</b> Additional-Stake Pockets
<b>SM1 =</b> Spare Tire Mount (Foldup)	<b>TB2 =</b> 24" Side Mount Toolbox
<b>CM1 =</b> 12" OC Crossmembers	<b>TB2A =</b> 36" Side Mount Toolbox
<b>DH =</b> Document Holder	<b>TB6 =</b> 48" Side Mount Toolbox
<b>PDA =</b> Charcoal Grey	<b>TB4 =</b> Riser Toolbox (upright)
<b>PG =</b> Double A Red	<b>DR1 =</b> 8' Dunnage Rack

Notes:


Signature: \_\_\_\_\_

--