



# Equipment Trailer

**ORIGINAL** Series

**QUALITY BUILD  
QUALITY PEOPLE**




4802 - 57th Ave., Two Hills, AB T0B 4K0 | Phone: 780-657-0008

[www.doubletrailers.ca](http://www.doubletrailers.ca)



# ORIGINAL

# Equipment Trailer



## EQ147-20



### TORSION OPTIONS:

TS7	7K GVW Torsion Upgrade
TS10	10K GVW Torsion Upgrade
TS12	12K GVW Torsion Upgrade
TS14	14K GVW Torsion Upgrade
TS16	16K GVW Torsion Upgrade
TS21	21K GVW Torsion Upgrade

### AXLE OPTIONS:

16	Upgrade 14K to 16K GVW
D16	Upgrade 14K to 16K GVW (2 Cyl)
Z1	Upgrade 14K to 21K GVW
Z42	Upgrade 21K to 24K GVW (3-8K Axles)
D	4" Drop Axle

### BRAKES:

S1	Surge Brakes (7K GVW)
S2	Surge Brakes (10K GVW)
E1	Electric over Hydraulic Brakes (All GVW's)

### TIRES & RIMS:

SP1	15" Spare Tire & Rim (ST205/75R15)
SP2	15" Spare Tire & Rim (ST225/75R15)
SP3	16" Spare Tire & Rim (ST235/80R16)
SP4	16" Dually Spare Tire & Rim (ST235/80R16)
SP5	16" Spare Tire & Rim (ST235/85R16)
SP6	16" Dually Spare Tire & Rim (ST235/85R16)
SP7	17.5" Single Spare Tire & Rim (235/75R17.5)

### HITCHES:

GN1	Gooseneck w/ 1-10K Jacks
GN2	Gooseneck w/ 2-10K Jacks
AD1	Adj. 2 5/16 Ball Coupler Upgrade (7K-10K GVW)
AD2	Adj. Pintle Ring Upgrade (7K-10K GVW)
AD3	Adj. 2-5/16 Ball Coupler Upgrade (20K-21K GVW)

### JACKS:

J2	Upgrade 8K to 12K Jack
J3	Add 2nd 12K Jack
J4	Upgrade 2-12K Jacks to 2 Speed Jacks

### RAMPS:

SR5	5' Stand Up or Slide in Ramps
SR5HD	5' HD Ramps - Upgrade
SRU6	Upgrade to 6' Stand Up Ramps
SR7	Upgrade to 6' Ramps w/ Mesh & Tapered Ends
SR8	3' Split Ramp Gate (requires DT2 or DT4 option)
SR9	4' Split Ramp Gate



### STANDARD FEATURES

<b>Safety Chains:</b>	5/16 Grade 70 chain w/ Grab Hooks	<b>Decking:</b>	2" Treated Wood fastened w/ 1/4" torx screws
<b>Width:</b>	102" Overall width	<b>Toolbox:</b>	None
<b>Wiring:</b>	Arctic wiring, soldered & enclosed in conduit	<b>Finish:</b>	Sand blasted & painted w/ PPG urethane paint
<b>Lights:</b>	Rubber mounted LED		

### MODEL:



CH77-16



EQ147-20



EQ217-24

	Main Frame	Deck Height	Pockets	Cross Members	Fenders	Coupler	Axle Size	Tire & Rim	Carrying Capacity	Tare Weight	Landing Gear
CH77-14' CH77-16' CH77-18' CH77-20'	5" channel	24"	1/4 preformed w/ full length 3/8" rubrail	3" Channel on 24" Centers	16g smooth (tear drop)	2 5/16 A-Frame	2,3.5k	225/75R 15	5,076lb 4,950lb 4,849lb 4,839lb	1924lb 2050lb 2161lb 2272lb	(1) 8k
CH107-14' CH107-16' CH107-18' CH107-20'	5" channel	24"	1/4 preformed w/ full length 3/8" rubrail	3" Channel on 24" Centers	16g smooth (tear drop)	2 5/16 A-Frame	2,5k	225/75R 15	7,950lb 7,803lb 7,700lb 7,580lb	2050lb 2197lb 2300lb 2420lb	(1) 8k
EQ127-14' EQ127-16' EQ127-18' EQ127-20'	6" channel	26-27"	3/16 preformed w/ full length 3/8" rubrail	3" Channel on 18" Centers	14g treadplate (83" between fenders)	2 5/16 A-Frame	2,6k	235/80R 16	9,850lb 9,685lb 9,570lb 9,455lb	2150lb 2315lb 2430lb 2545lb	(1) 8k
EQ147-14' EQ147-16' EQ147-18' EQ147-20' EQ147-22' EQ147-24'	6" channel 7" channel	26-27"	3/16 preformed w/ full length 3/8" rubrail	3" Channel on 18" Centers	14g treadplate (83" between fenders)	2 5/16 Adjustable	2,7k	235/80R 16	11,810lb 11,645lb 11,530lb 11,292lb 11,170lb 11,030lb	2190lb 2355lb 2470lb 2708lb 2830lb 2970lb	(1) 12k