



Pro Series

Roll Off Trailer 14,000lb GVW

Ordered By: _____

Dealer: _____

PO#: _____

Date: _____

Standard Features:

Coupler:	2-5/16" Adjustable Channel Mount	Sub Frame:	7" channel
Safety Chains:	5/16" Grade 70 w/Grab Hooks	Fenders:	14 Gauge Tread Plate
Width:	102" Overall, 83" Inside Box	Wiring:	Arctic Wiring, Soldered & Enclosed in Conduit
Deck Height:	29"	Lights:	LED, Rubber Mounted
Axles:	Electric Brakes, Grease Hubs, 8 Stud	Toolbox:	A-Frame (Hydraulic Housing)
Suspension:	Leaf Springs w/Equalizers	Finish:	Sand Blast, Prime, Paint w/PPG Urethane
Tires & Rims	10 Ply Tires w/Modular Rims	Tarp:	Included
Main Frame:	8" Wide Flange Beam		

MODEL:

Quantity: _____

****NOTE** Only one type of trailer per order form.**

	Side Height	Main Frame	Axle Size	Tire & Rim	Tare Weight	Carrying Capacity Cubic Yard/lb	Hoist	Landing Gear
RO147-14	8"	8" WF	2:7000lb	235/80R16	4950	12 Yards/ 10,606lbs	7 Ton	1:12,000lb

OPTIONS:

270ET =	2-7000Lb Elec/Tor	H3 =	Upgrade Hoist -7 to 10 Ton
CPR =	Channel Mount Pintle Ring	DH =	Document Holder
SP3 =	Spare-ST235/80R16-10ply-single	P5 =	Quick Connect Power Cable
SP5 =	Spare-ST235/85R16-14ply-single	P6 =	Solar Panel
USP5 =	ST235/85R16-14ply Upgrade	CW2 =	Quick Charge - 12v (20amp)
AW2 =	Alum wheel upgrade-16"	WRK =	Wireless remote for Pwrpack
PDA =	Double A Red	CP7 =	Commercial Plug
PG =	Charcoal Grey	CW1 =	110 Inverter Charger
PCST =	Custom Bin Color (specify below)	AB1 =	Additional Battery
HD15 =	Additional 15' DECK (14-16K GVW)	B15 =	Additional 12 Yard BIN (14-16K GVW)

Notes:

	Signature: