



EXCEL Series

Carhauler Trailer - 7000-10000lb GVW

Ordered By: _____

Dealer: _____

PO#: _____

Date: _____

Standard Features:

Coupler:	2-5/16" A Frame Coupler	Fenders:	14 ga Tread Plate
Safety Chains:	5/16" Grade 70 w/Grab Hooks	Pockets:	Preformed - 3/16", no rub rail
Width:	102" Overall , 83" Between Fenders	Cmembers:	Channel - 3" on 24" centers
Deck Height:	26-27"	Wiring:	Arctic Wiring, Soldered & Enclosed in Conduit
Axles:	Electric Brakes, Grease Hubs, 5 Stud	Lights:	LED, Rubber Mounted
Suspension:	Double Eye Leaf Springs w/Equalizers	Decking:	Spruce - 2" Treated
Tires & Rims:	8 Ply Tires w/White Modular Rims	Toolbox:	Not Included
Main Frame:	Channel (See Below)	Finish:	Sand Blast, Prime, Paint w/PPG Urethane
Ramps:	5' Slide in Standard	Rear Stabilizers:	Not Included

MODEL:

****NOTE** Only one type of trailer per order form.**

Quantity:

Select Model	Main Frame	Axle Size	Tire & Rim	Tare Weight	Carrying Capacity	Landing Gear
ECH77-12	5" Channel	2:3500lb	205/75R15	1808lb	5,711lbs	1:8000lb
ECH77-14	5" Channel	2:3500lb	205/75R15	1924lb	5,584lbs	1:8000lb
ECH77-16	5" Channel	2:3500lb	205/75R15	2050lb	5,445lbs	1:8000lb
ECH77-18	5" Channel	2:3500lb	205/75R15	2161lb	5,323lbs	1:8000lb
ECH77-20	5" Channel	2:3500lb	205/75R15	2272lb	5,201lbs	1:8000lb
ECH77-22	5" Channel	2:3500lb	205/75R15	2388lb	5,073lbs	1:8000lb
ECH77-24	5" Channel	2:3500lb	205/75R15	2504lb	4,946lbs	1:8000lb

OPTIONS:

250ES = 2-5000Lb Elec/Spr	DT2 = 2' Dovetail w Tread Plate
SP1 = Spare-205/75R15-6ply (3500Lb)	SRU5 = 5' Stand Up Ramps
SP2 = Spare-ST225/75R15-8ply (5000Lb)	R3W = Weld On 3" D Ring
AW1 = Alum wheel upgrade-15"	R4W = Weld On 4" D Ring
TB1 = A Frame Toolbox	R4R = Removable 4" D ring
PDA = Double A Red	R3R = Removable 3" D ring
PG = Charcoal Grey	SM2 = Side spare Mount (Weld on)
DH = Document Holder	SM3 = Side spare Mount (Removeable)
ERR = Add Rub Rail to Excel	RS1 = Rear Stabilizers (Tube)

Notes:

Signature: _____