



Pro Series

Cushion Tilt Trailer 14,000lb GVW

Ordered By: _____

Dealer: _____

PO#: _____

Date: _____

Standard Features:

Coupler:	2-5/16" Adjustable Channel Mount	Fenders:	14 ga Tread Plate
Safety Chains:	5/16" Grade 70 w/Grab Hooks	Pockets:	Preformed - 3/16" w/Full Length 1/4" Rubrail
Width:	102" Overall, 83" Between Fenders	Cmembers:	Channel - 3" on 18" Centers
Deck Height:	22-23"	Wiring:	Arctic Wiring, Soldered & Enclosed in Conduit
Axles:	Electric Brakes, Grease Hubs, 8 Stud	Lights:	LED, Rubber Mounted
Suspension:	Rubber Torsion, Drop	Decking:	Spruce - 2" Treated
Tires & Rims	10 Ply Tires w/Modular Rims	Toolbox:	Not Included
Main Frame:	See Below	Finish:	Sand Blast, Prime, Paint w/PPG Urethane
Tilt:	Single Cylinder w/Damper Lever		

MODEL:

Quantity: _____

****NOTE** Only one type of trailer per order form.**

Select Model	Main Frame	Axle Size	Tire & Rim	Tare Weight	Carrying Capacity	Landing Gear
CT147-18	6" Channel	2:7000lb	235/80R16	3530lb	12026lb	1:12,000lb
CT147-20	7" Channel	2:7000lb	235/80R16	3750lb	11806lb	1:12,000lb
CT147-22	7" Channel	2:7000lb	235/80R16	3970lb	11586lb	1:12,000lb
CT147-24	7" Channel	2:7000lb	235/80R16	4190lb	11366lb	1:12,000lb

OPTIONS:

SP3 = Spare-ST235/80R16-10ply-single	PS1 = Pipe Spools (Between Pockets)
SP5 = Spare-ST235/85R16-14ply-single	W4P = Removable 3 Bar Winch
USP5 = ST235/85R16-14ply Upgrade	R4W = Weld on 4" D Ring
AW2 = Alum wheel upgrade-16"	R4R = Removable 4" D Ring
CPR = Channel Mount Pintle Ring	P4X = 4ea Extra Stake Pockets
CM1 = 12" OC Crossmembers	P1X = Additional-Stake Pockets
DH = Document Holder	SM2 = Side spare Mount (Weld on)
PG = Charcoal Grey	SM3 = Side spare Mount (Removeable)
PDA = Double A Red	TB1 = A Frame Toolbox
FG1 = Fender guards (pipe)	

Notes:

	Signature: